

Single Plate Universal EHS Racing Kits



100% Satisfaction Guaranteed

1975 N US Highway 1, Rockingham, NC 28379
www.ehsracing.com 866-997-2345



100% Satisfaction Guarantee

Policy applies only to products manufactured directly by or directly for EHS Racing. The time period for this policy is 30 days after delivery of items, if for any reason you the customer are unhappy with a product it can be returned to EHS Racing no questions asked. If the product was sold directly by EHS Racing we will provide money back, store credit, whatever the customer prefers. If item was purchased through a dealer or distributor we can only offer a trade allowance towards another item equal to the same value. If cash back credit is needed it must be returned to the original place of purchase. We do not cover or refund return shipping expenses and original shipping expenses, these will be forfeited by customer. After 30 days an EHS Racing product can still be returned for store credit only up until 60 days from time of delivery. After 60 days no returns will be accepted unless there is a manufacturer defect, but the decisions solely lies with EHS Racing whether an item is defective or not.

Agreement:

EHS Racing manufactures after market parts and accessories that can be used for racing. These parts are intended for use by professionals that have proper experience in operating the equipment that those products were designed for. These products are to be installed by qualified technicians whether it be yourself or dealer, by installing any products manufactured by EHS Racing or directly for EHS Racing you assume all liability for any damages direct or consequential resulting from the installation. EHS Racing's liability extends to product replacement only.

Parts Included:

Quantity	Description	Part Number
<i>(Installation Instructions are Generic for all universal kits so all quantity's and part numbers are not listed)</i>		
1	Aluminum Plate	
1	Pre-Filter	
1	Rubber Gasket	
1	Aluminum Backing Plate	
	1/4X20-3/4 Socket Cap Bolts	2092
	1/4X20 Stainless Nuts	2098
	1/4 Stainless Washers	2097

Installation Instructions

First we would like to thank you for purchasing a quality EHS Racing product. We take pride in everything we design if for any reason you're unhappy please call our shop and let us know. We stand behind our 100% Satisfaction Guarantee.

*** Installing this kit for the purposes of adding air to an engine may result in a leaner condition than before. Before installation proper testing should be performed by a mechanic with proper experience and knowledge . A plug check is highly recommended to see if a lean condition is present.**

- (Remember these are generic instructions that cover all of our universal kits some changes may be necessary)** Installation, what you need is a marker, drill with 1/4" bit, jig saw, a wood blade works great for plastic or another type of a saw to cut the hole out, a 7/16" open end wrench, a 3/16" Allen wrench, sand paper, chisel ,and a pair of side cutters. (Fig 1)
- Place the plate on the surface so it will lay flat and seal when mounting is complete. Pay attention to the backside of the mounting area and make sure there will be no obstructions that can not be removed or will prevent installation. Also consider you will need to access the back side to secure the nuts and washers, with the filter covering the hole your about to cut out. (Fig 2)

- Drill through the aluminum plate into the mounting surface, if possible put one of the bolts through the hole and secure it with a nut. Next drill a second hole opposite of first and install nut and bolt, then proceed to drill the rest of the holes this is to make sure the plate stays in the same spot.
- Once the holes are drilled outline the hole that you are going to cut out. (Fig 3)
- Take the plate off and cut the hole out, usually the recommended tool is a jigsaw or dremel if your are mounting to plastic a jig saw with a wood blade is best. HINT: It's easiest to drill the corners with a bigger drill bit first, before cutting. (Fig 4)
- Now that the hole is cut, remove any molded parts that interfere with the bolts. Then file and sand all the edges and make sure everything is smooth or else the filter can rip over time.
- Once smooth take the filter, and plate assemble together. Order recommended: mounting location > gasket > filter > plate. (Fig 5)
- Once assembled position over the hole and line up the holes, and bolt everything together and your ready to go. (Fig 6)

Warranty

All EHS Racing products manufactured by EHS Racing or directly for EHS Racing carry a 1 (ONE) Year warranty from the time of purchase for manufacture defects and workmanship. The decision that a product is defective solely lies with EHS Racing to determine. If the product is deemed defective a new replacement will be exchanged. In the event that a product is discontinued, out of stock, or not able to be replaced EHS Racing retains the right to substitute another product of equal or greater value.

Fig. 1

Fig. 2

Fig.3

Fig. 4

Fig. 5

Fig. 6

